

US005431496A

United States Patent [19]

Balteau et al.

Patent Number: [11]

5,431,496

Date of Patent: [45]

Jul. 11, 1995

| [54] | MULTIPLE CHAMBER CONTAINER | | | | | | |
|-------------------------------|---|---|--|--|--|--|--|
| [75] | Inventors: | Patrick Balteau, St Denis; Dirk Faict, Assenede; Francesco Peluso, Heverlee, all of Belgium | | | | | |
| [73] | Assignee: | Baxter International Inc., Deerfield, Ill. | | | | | |
| [21] | Appl. No.: | 295,363 | | | | | |
| [22] | Filed: | Aug. 24, 1994 | | | | | |
| Related U.S. Application Data | | | | | | | |
| [63] | Continuation of Ser. No. 6,339, Jan. 19, 1993, abandoned. | | | | | | |
| | | | | | | | |
| [58] | Field of Sea | 383/38, 41, 904, 906; 206/219; 604/410 | | | | | |
| [56] | References Cited | | | | | | |
| U.S. PATENT DOCUMENTS | | | | | | | |
| | 3,304,977 2/1 3,542,032 11/1 4,396,382 8/1 4,396,383 8/1 4,458,733 7/1 4,465,438 8/1 | 1983 Goldhaber . 1983 Hart . 1984 Lyons . | | | | | |

| 4,484,920 | 11/1984 | Kaufman et al |
|-----------|---------|----------------------------|
| 4,529,102 | 7/1985 | Quinn et al 604/410 X |
| 4,608,043 | 8/1986 | Larkin 206/219 X |
| 4,630,727 | 12/1986 | Feriani et al |
| 4,997,083 | 3/1991 | Loretti et al 383/38 X |
| 5,061,236 | 10/1991 | Sutherland et al 604/410 X |
| 5,261,532 | 11/1993 | Fauci 383/38 X |
| | | |

FOREIGN PATENT DOCUMENTS

| 0132632 | 2/1985 | European Pat. Off 206/219 |
|-----------|---------|---------------------------|
| 3238649A1 | 4/1984 | Germany . |
| 582101 | 11/1976 | Switzerland 206/219 |
| 0458538 | 12/1936 | United Kingdom 383/38 |

Primary Examiner-Jes F. Pascua Attorney, Agent, or Firm-Thomas S. Borecki; Charles R. Mattenson; Robert M. Barrett

ABSTRACT [57]

A multiple chamber container for mixing and administering a plurality of products. The container has at least two chambers separated by a seal line. A frangible connector is situated between the two chambers for mixing the products contained within the chambers as desired. Each chamber has at least one port for filling of product into the chamber. The ports are located on the same exterior side of the container such that the chambers can be filled without folding the bag and by using existing filling equipment.

13 Claims, 2 Drawing Sheets

